



- Elektrostatisch pulverbeschichtet
- Metall-Außenrahmen
- Aluminium-Innenrahmen
- 30° vertikal schwenkbar
- 36° Abstrahlwinkel

- Electrostatic powder coated
- Metal outer frame
- Aluminium inner frame
- Adjustability allows 30° rotation for the vertical axis
- 36° beam angle

Farbe: sw (04), weiß (03), RAL9006 (00)



Color: Black, white, metallic grey

LED

Standard Version				
LAN4021033	1x3,9W	LED modul	GU10	440 gr.
LAN4021034	1x5,5W	LED modul	GU10	440 gr.



Lichtkurven: www.lamp83.de
Light curves: www.lamp83.de



IP 20



850°



LED

Standard Version				
LAN4022033	2x3,9W	LED modul	GU10	710 gr.
LAN4022034	2x5,5W	LED modul	GU10	710 gr.

Lichtkurven: www.lamp83.de
Light curves: www.lamp83.de



IP 20

850°






LED

Standard Version				
LAN4023033	3x3,9W	LED modul	GU10	995 gr.
LAN4023034	3x5,5W	LED modul	GU10	995 gr.

Lichtkurven: www.lamp83.de
Light curves: www.lamp83.de



Farbtemperatur Color Temperature K	Energieverbrauch Consumed power W	Lumen-Wert Lumen output lm	Min. Farbwiedergabe Min. color rendering ra
2700	3,9	230	80
4000	3,9	230	80
2700	5,5	350	80
4000	5,5	350	80

LED Daten gelten für das Einzelmodul.
LED information is only for single module.