


## OPTIO EINBAU / RECESSED



W • lm	Standard	DALI Dimm	L (mm)	∅ (mm)
2 W • 200 lm	LAN3015030	LAN3015040*	63	45x55
4 W • 400 lm	LAN3015031	LAN3015041*	103	45x95
8 W • 850 lm	LAN3015032	LAN3015042	183	45x175
20 W • 2100 lm	LAN3015034	LAN3015044	621	45x613

\* Diese Produkte haben gruppierte Treiberanwendungen. / These products have group driver application.



- Funktionales, innovatives, effizientes und komfortables Design
- Blendfrei ( $UGR \leq 19$ ) und perfekte Lichtlenkung aus Linsenoptik- und Reflektorkombination
- Je nach Leuchte können 1-20 einzelne LEDs in Reihe mit je 2W verwendet werden
- Energieeffizienzklasse A + L80 50.000 Std. Lebensdauer
- 24 ° - 40 ° Abstrahlwinkel
- 3000K - 4000K (CCT) Farbtemperatur SDCM 3
- DALI Dimm Option, geeignet für Automatisierung (optional)

- Functional, innovative, efficient and comfortable design
- Low glare effect ( $UGR \leq 19$ ) and perfect light control with optical lens and anodized metal reflector combination
- Depending on the luminaire, possibility to use between 1-20 single LEDs, each 2W
- Class A+ energy efficient & 50.000 hours life time LED
- 24° – 40° beam angle
- 3000K – 4000K (CCT) light color temperature SDCM 3
- DALI dim option, suitable for automation (optional)

Farboptionen / color options: ● ○ ●

3000K - 4000K • 400 - 1350 gr



IP 20

850°

