



- Elektrostatisch pulverbeschichtet
- Druckguss-Außenrahmen
- Aluminium-Körper
- Aluminium-Kühlkörper stranggepresst
- Polymer-Innenrahmen
- schwenkbarer Aluminium-Innenrahmen stranggepresst
- 15° - 24° - 30° - 36° - 45° - 60° Abstrahlwinkel mit Facetten-Reflektor aus 99,8% purem Aluminium
- extra weißes Sicherheitsglas
- Electrostatic powder coated
- Die-cast outer frame
- Aluminium body
- Extruded aluminium heat sink
- Polymer inner frame
- Adjustable extruded aluminium inner frame
- 15° - 24° - 30° - 36° - 45° - 60° beam angle options with %99,8 pured polished pattern aluminium reflector
- Extra clear tempered protection glass

Color: Black, white, metallic grey

Farbe: sw (04), weiß (03), RAL9006 (00)



LED



Standard Version			
LAN4521130	1x25W	LED modul	1500 gr.
LAN4521131	1x30W	LED modul	1500 gr.
LAN4521132	1x40W	LED modul	1500 gr.

DALI DIMM Version			
LAN4521140	1x25W	LED modul	1550 gr.
LAN4521141	1x30W	LED modul	1550 gr.
LAN4521142	1x40W	LED modul	1550 gr.

1 Std. Akku Batterie Pack / With 1 hour battery pack			
LAN4521150	1x25W	LED modul	2000 gr.
LAN4521151	1x30W	LED modul	2000 gr.
LAN4521152	1x40W	LED modul	2000 gr.

3 Std. Akku Batterie Pack / With 3 hours battery pack			
LAN4521160	1x25W	LED modul	2100 gr.
LAN4521161	1x30W	LED modul	2100 gr.
LAN4521162	1x40W	LED modul	2100 gr.

Lichtkurven: www.lamp83.de
Light curves: www.lamp83.de



ERL

CE

IP 20

850°



LED

Farbtemperatur Color Temperature K	Energieverbrauch Consumed power W	Lumen-Wert Lumen output lm (tc: 55°C)	Min. Farbwiedergabe Min. color rendering ra
3000	25	2800	80
4000	25	3000	80
3000	30	3750	80
4000	30	4000	80
3000	40	4350	80
4000	40	4650	80