



- Elektrostatisch pulverbeschichtet
- Metall-Körper und Rahmen
- Plexiglas

- Electrostatic powder coated
- Metal body and frame
- Plexiglass

Farbe: sw (04), weiß (03), RAL9006 (00)

Color: Black, white, metallic grey

Standard Version						
LDL5008001	1x40W	T5 FC	2Gx13	a:450 mm.	∅b:440 mm.	3265 gr.
LDL5008002	1x55W	T5 FC	2Gx13	a:450 mm.	∅b:440 mm.	3265 gr.

LED

Standard Version						
LDL5010030	1x25W	LED modul		a:550 mm.	∅b:540 mm.	9000 gr.
LDL5010031	1x35W	LED modul		a:550 mm.	∅b:540 mm.	9000 gr.

DALI DIMM Version						
LDL5010040	1x25W	LED modul		a:550 mm.	∅b:540 mm.	9000 gr.
LDL5010041	1x35W	LED modul		a:550 mm.	∅b:540 mm.	9000 gr.



Standard Version						
LDL5011030	1x25W	LED modul		a:650 mm.	∅b:640 mm.	11000 gr.
LDL5011031	1x35W	LED modul		a:650 mm.	∅b:640 mm.	11000 gr.

DALI DIMM Version						
LDL5011040	1x25W	LED modul		a:650 mm.	∅b:640 mm.	11000 gr.
LDL5011041	1x35W	LED modul		a:650 mm.	∅b:640 mm.	11000 gr.

Standard Version						
LDL5012030	1x54W	LED modul		a:950 mm.	∅b:940 mm.	19000 gr.
LDL5012031	1x80W	LED modul		a:950 mm.	∅b:940 mm.	19000 gr.

DALI DIMM Version						
LDL5012040	1x54W	LED modul		a:950 mm.	∅b:940 mm.	19000 gr.
LDL5012041	1x80W	LED modul		a:950 mm.	∅b:940 mm.	19000 gr.

Lichtkurven: [www.lamp83.de](http://www.lamp83.de)  
Light curves: [www.lamp83.de](http://www.lamp83.de)



Farbtemperatur Color Temperature K	Energieverbrauch Consumed power W	Lumen-Wert Lumen output lm (tc: 45°C)	Min. Farbwiedergabe Min. color rendering ra
3000	25	3350	80
4000	25	3550	80
3000	35	4250	80
4000	35	4550	80
3000	54	7850	80
4000	54	8350	80
3000	80	9900	80
4000	80	10550	80