



- Elektrostatisch pulverbeschichtet
- Metall-Körper
- Plexiglas
- Anbaumontage

- Electrostatic powder coated
- Metal body
- Plexiglass
- With base

Farbe: sw (04), weiß (03), RAL9006 (00)


Color: Black, white, metallic grey

LED

Standard Version				
LSK1214030	1x25W	LED modul	a:480 mm.	8000 gr.
LSK1214031	1x35W	LED modul	a:480 mm.	8000 gr.
DALI DIMM Version				
LSK1214040	1x25W	LED modul	a:480 mm.	8000 gr.
LSK1214041	1x35W	LED modul	a:480 mm.	8000 gr.

Standard Version				
LSK1215030	1x25W	LED modul	a:600 mm.	11000 gr.
LSK1215031	1x35W	LED modul	a:600 mm.	11000 gr.
DALI DIMM Version				
LSK1215040	1x25W	LED modul	a:600 mm.	11000 gr.
LSK1215041	1x35W	LED modul	a:600 mm.	11000 gr.

Standard Version				
LSK1216030	1x54W	LED modul	a:900 mm.	18000 gr.
LSK1216031	1x80W	LED modul	a:900 mm.	18000 gr.
DALI DIMM Version				
LSK1216040	1x54W	LED modul	a:900 mm.	18000 gr.
LSK1216041	1x80W	LED modul	a:900 mm.	18000 gr.



Lichtkurven: www.lamp83.de
Light curves: www.lamp83.de



Farbtemperatur Color Temperature K	Energieverbrauch Consumed power W	Lumen-Wert Lumen output lm (tc: 45°C)	Min. Farbwiedergabe Min. color rendering ra
3000	25	3350	80
4000	25	3550	80
3000	35	4250	80
4000	35	4550	80
3000	54	7850	80
4000	54	8350	80
3000	80	9900	80
4000	80	10550	80