


CO LIGHT SYSTEM



SILVER Einbauleuchten Panel / With SILVER Recessed Panel

W • lm	Standard	DALI Dimm	Notfall Kit Emergency Kit
2x(20 W•2710 lm)	LSK2503230	LSK2503240	LSK2503260
2x(30 W•4350 lm)	LSK2503231	LSK2503241	LSK2503261
2x(40 W•5220 lm)	LSK2503232	LSK2503242	LSK2503262

W • lm	Holz / Wood	DALI Dimm	Notfall Kit Emergency Kit
2x(20 W•2710 lm)	LSK2504230	LSK2504240	LSK2504260
2x(30 W•4350 lm)	LSK2504231	LSK2504241	LSK2504261
2x(40 W•5220 lm)	LSK2504232	LSK2504242	LSK2504262



Helle Kiefer / *Light pine*
BY101401



Dunkle Kiefer / *Dark Pine*
BY101402



Ahorn / *Maple*
BY101403



Walnuss / *Walnut*
BY101404

- Panel Maße: 680x1100mm, Montagehöhe max. 3m
- Verschiedene Holzoptiken
- Panel für Akzentbeleuchtung, verschiedene LAMP83 Leuchten integrierbar
- 2x20W, 2x30W oder 2x40W SILVER Einbauleuchten, die auf der vertikalen Achse 20° schwenkbar sind
- Energieeffizienzklasse A++ , L80 50.000 Std. LED Lebensdauer
- Farbtemperatur 3000K – 4000K (CCT)
- DALI dimm Option, geeignet für Automatisierung (optional)
- Notfall-Kit 3 Stunden (optional)

- Panel that can be suspended up to 3 meters with a size 680x1100mm
- Different wooden-like paint options on request
- Integrated electrotrack option for accent lighting (It can be used with the desired LAMP83 spotlight)
- 2x20W, 2x30W or 2x40W SILVER recessed product option that could be tilted until 20° over vertical axis
- A++ energy efficiency, L80 50.000 hours life time LED
- CCT light color temperature: 3000K – 4000K
- DALI dim option, suitable for automation (optional)
- 3 hours emergency battery kit (optional)

Farboptionen / color options: 

3000K - 4000K • 6850 gr



IP 20

850°

