

## ARK-XS PENDEL / PENDANT



W • lm	Standard	DALI	Holz/Wood	L (mm)
22 W • 3100 lm	LSK2612005	LSK2612045	LSK2613005	1182
32 W • 4250 lm	LSK2612006	LSK2612046	LSK2613006	1182
28 W • 3900 lm	LSK2612007	LSK2612047	LSK2613007	1473
40 W • 5300 lm	LSK2612008	LSK2612048	LSK2613008	1473
39 W • 5450 lm	LSK2612011	LSK2612051	LSK2613011	2055
56 W • 7400 lm	LSK2612012	LSK2612052	LSK2613012	2055
44 W • 6250 lm	LSK2612013	LSK2612053	LSK2613013	2346
64 W • 8450 lm	LSK2612014	LSK2612054	LSK2613014	2346
50 W • 7000 lm	LSK2612015	LSK2612055	LSK2613015	2637
72 W • 9500 lm	LSK2612016	LSK2612056	LSK2613016	2637

W • lm	UGR≤19 Standard	UGR≤19 DALI	UGR≤19 Holz/Wood	L (mm)
16 W • 2250 lm	LSK2615005	LSK2615045	LSK2616005	1182
22 W • 3100 lm	LSK2615006	LSK2615046	LSK2616006	1182
20 W • 2850 lm	LSK2615007	LSK2615047	LSK2616007	1473
28 W • 3900 lm	LSK2615008	LSK2615048	LSK2616008	1473
28 W • 4000 lm	LSK2615011	LSK2615051	LSK2616011	2055
39 W • 5450 lm	LSK2615012	LSK2615052	LSK2616012	2055
32 W • 4550 lm	LSK2615013	LSK2615053	LSK2616013	2346
44 W • 6250 lm	LSK2615014	LSK2615054	LSK2616014	2346
36 W • 5150 lm	LSK2615015	LSK2615055	LSK2616015	2637
50 W • 7000 lm	LSK2615016	LSK2615056	LSK2616016	2637

## HOLZVARIANTEN / WOOD COLOR OPTIONS



Helle Kiefer / Light pine  
BY101401




Dunkle Kiefer / Dark Pine  
BY101402



Ahorn / Maple  
BY101403



Walnuss / Walnut  
BY101404



- ARK XS Pendel ist nicht für Betondecken geeignet
- Holzoptik auf Anfrage erhältlich
- Standardpendellänge 3m
- Energieeffizienzklasse A, L80 50.000 Std. Lebensdauer
- Verschiedene Leistungsstärken zwischen 16 - 72W
- Farbtemperatur 3000K - 4000K (CCT)
- Effiziente, homogene, blendfreie Beleuchtung
- UGR ≤ 19 mit mikroprismatischem Diffusor
- T, L, X und rechteckige Profillösungen oder spezielle Längen auf Anfrage
- DALI dimm Option, geeignet für die Automatisierung (optional)

- ARK XS pendant version is not applicable on concrete ceilings
- Wooden-like paint option on request
- Usual pendant length 3m
- Class A energy efficient, L80 50.000 hours life time
- LED power 16 - 72W
- 3000K - 4000K (CCT) light color temperature
- Efficient, homogeneous lighting thanks to a special diffusor
- Low glare effect with microprismatic diffuser (UGR ≤ 19)
- Different production possibilities in special lengths or T, L, X and rectangular shapes
- DALI dim option, suitable for automation (optional)

Farboptionen / color options: ● ○ ● ●

3000K - 4000K • 2300 - 7000 gr



IP 20

850°

