

OPTIO PENDEL / PENDANT



W • lm	Standard	DALI Dimm	L (mm)
24 W • 2500 lm	LSK3011030	LSK3011040	1200
32 W • 3350 lm	LSK3011031	LSK3011041	1500
40 W • 4150 lm	LSK3011032	LSK3011042	2000

KOMBINATIONEN HOLZOPTIK /
WOOD COLOR COMBINATIONS:


Helle Kiefer / Light pine
 BY101401

Ahorn / Maple
 BY101403

Dunkle Kiefer / Dark Pine
 BY101402

Walnuss / Walnut
 BY101404

W • lm	Holz/Wood	DALI Dimm	L (mm)
24 W • 2500 lm	LSK3012030	LSK3012040	1200
32 W • 3350 lm	LSK3012031	LSK3012041	1500
40 W • 4150 lm	LSK3012032	LSK3012042	2000



- Einbau-, Anbau-, Pendel- und Lamellenversionen
- Funktionales, innovatives, effizientes und komfortables Design
- Blendfrei ($UGR \leq 19$) und perfekte Lichtlenkung aus Linsenoptik- und Reflektorkombination
- Je nach Leuchte können 1-20 einzelne LEDs in Reihe mit je 2W verwendet werden
- Energieeffizienzklasse A + L80 50.000 Std. Lebensdauer
- 24 ° - 40 ° Abstrahlwinkel
- 3000K - 4000K (CCT) Farbtemperatur SDCM 3
- DALI Dimm Option, geeignet für Automatisierung (optional)

- Recessed, surface mounted, pendant and lamella versions
- Functional, innovative, efficient and comfortable design
- Low glare effect ($UGR \leq 19$) and perfect light control with optical lens and anodized metal reflector combination
- Depending on the luminaire, possibility to use between 1-20 single LEDs, each 2W
- Class A+ energy efficient & 50.000 hours life time LED
- 24° – 40° beam angle
- 3000K – 4000K (CCT) light color temperature SDCM 3
- DALI dim option, suitable for automation (optional)

Farboptionen / color options:

3000K - 4000K • 3600 - 5450 gr



IP 20

850°

