

R-FLEX STRAHLER / SPOTLIGHT




W	LED lm	Standard	DALI Dimm
25 W	3100 lm	LSP1410130	LSP1410140
30 W	3680 lm	LSP1410131	LSP1410141

Die semi-eingebauten Leuchtenköpfe sind 90° vertikal schwenkbar, um einerseits Allgemeinbeleuchtung zu schaffen und andererseits mit fokussiertem Licht ideal Produkte oder Objekte in Szene zu setzen. Der R-FLEX Strahler verfügt über einen Track-In Adapter, somit bietet die Serie die komplette Vielfalt die ein Projekt fordert.

Semi-recessed products that allows adjustability up to 90° in vertical axis and 350° in horizontal axis on one hand serve for requirements of general lighting, on the other hand create focussed lighting over the products or objects to provide ideal solution to grab the attention. R-FLEX spotlight, available with an integrated track adaptor, offers the possibility to meet complete lighting requirements of a place within the same product family.

Technische Zeichnung /
Technical drawing (mm):



TECHNISCHE EIGENSCHAFTEN / TECHNICAL SPECIFICATIONS:

Gehäuse / Housing:	Aluminium
Oberflächenschutz / Surface protection:	Elektrostatisch pulverbeschichtet / Electrostatic powder coated
Gehäusefarbe / Color housing:	RAL9005, RAL9016, RAL9006
Verstellbarkeit / Adjustability:	330° horizontal drehbar, 90° vertikal schwenkbar / Adjustability 330° in horizontal axis and 90° in vertical axis
Abdeckung / Cover:	Glas extra weiss / Glass extra white
Lichtverteilung / Lighting distribution:	Reflektor / Reflector
Abstrahlwinkel / Beam angle:	30° - 45° - 60°
Blendlevel / Glare effect:	N/A
LED Lebensdauer / LED life time:	L80 50.000h
Farbtemperatur / Color temperature (Kelvin):	3000K / 4000K
Farbwiedergabe / Color rendering index CRI (Ra):	≥90
Mac Adam:	Step 2-3
Energieeffizienzklasse / Energy efficiency class:	A++
Photobiologische Sicherheit / Photobiological safety EN 62471	RG 0-1
Betriebsgerät / Control gear:	Inkl. Kit
Betriebsspannung / Operating voltage:	220V AC ~ 240V AC
Betriebsfrequenz / Operating frequency:	50 ~ 60 Hz
Optionen / Options:	DALI Dimm, Casambi, Automation

Farboptionen / Color options:



3000K - 4000K • 1020 gr

