


SILVER STRAHLER / SPOTLIGHT



W • lm	Standard	DALI Dimm
20 W • 2710 lm	LSP1424001	LSP1424101
30 W • 4350 lm	LSP1424010	LSP1424110
40 W • 5220 lm	LSP1424023	LSP1424123
50 W • 6300 lm	LSP1424033	LSP1424133



COLOR EDITION:



CL01

CL02

CL03

CL04

CL05

CL06

- Energieeffizienzklasse A++, 1. Platz des 'energy efficiency awards'
- Horizontale Kit Box Option
- L 80 50.000 Std. LED Lebensdauer
- 2.710 – 6.300 Lumen bei 20W - 50W Leistung
- 15° – 30° – 45° – 60° Abstrahlwinkel mit spezieller Reflektortechnik
- Farbtemperatur 3000K - 4000K (CCT) SDCM 3
- DALI Dimm Option, geeignet für Automatisierung (optional)

- A++ energy efficiency, awarded 1st place trophy for energy efficiency by ICI (Istanbul Chamber Of Industry)
- Horizontal kit box option
- L80 50.000h life time LED power between 20 - 50W
- LED lumen output between 2.710 – 6.300 lm
- Special designed reflector with 15° – 30°– 45°–60° angles
- CCT light color temperature: 3000K – 4000K SDCM 3
- DALI dim option, suitable for automation (optional)

Standard Farboptionen / standard color options: CL04 ● CL05 ○ CL06 ●

3000K - 4000K • 1600 - 1750 gr



IP 20

850°

