



- Elektrostatisch pulverbeschichtet
- Aluminium-Kühlkörper
- Plexiglas-Körper
- Anbaumontage

- *Electrostatic powder coated*
- *Aluminium heat sink*
- *Plexiglass body*
- *With base*

Farbe: Rot, Grün, Blau, Orange

Color: Red, green, blue, orange


LED

Standard Version			
LSU1004030	2x5W	E27 - A45 / LED	2070 gr.

Standard Version			
LSU1004031	1x10W	LED modul	2700 gr.
LSU1004032	1x15W	LED modul	2700 gr.

DALI DIMM Version			
LSU1004041	1x10W	LED modul	2750 gr.
LSU1004042	1x15W	LED modul	2750 gr.

Treiber der Leuchte ist in der Decke zu platzieren.
 Deckenausschnitt: Ø90mm.
*Driver of the luminaire is placed within the false ceiling.
 Hole diameter for "driver" is Ø:90 mm.*



Lichtkurven: www.lamp83.de
 Light curves: www.lamp83.de


LED

Standard Version			
LSU1004130	2x10W	E27 - A60 / LED	3070 gr.

Standard Version			
LSU1004131	1x15W	LED modul	3700 gr.
LSU1004132	1x20W	LED modul	3700 gr.

DALI DIMM Version			
LSU1004141	1x15W	LED modul	3750 gr.
LSU1004142	1x20W	LED modul	3750 gr.

Treiber der Leuchte ist in der Decke zu platzieren.
 Deckenausschnitt: Ø90mm.
*Driver of the luminaire is placed within the false ceiling.
 Hole diameter for "driver" is Ø:90 mm.*



Lichtkurven: www.lamp83.de
 Light curves: www.lamp83.de

Farbtemperatur Color Temperature K	Energieverbrauch Consumed power W	Lumen-Wert Lumen output lm (tj: 85°C)	Min. Farbwiedergabe Min. color rendering ra
2800	5	470	80
2700	10	800	80
3000	10	1300	80
4000	10	1300	80
3000	15	1900	80
4000	15	1900	80
3000	20	2650	80
4000	20	2650	80

