



- Elektrostatisch pulverbeschichtet
- Aluminium-Kühlkörper
- Plexiglas-Körper
- Anbaumontage

- Electrostatic powder coated
- Aluminium heat sink
- Plexiglass body
- With base

Farbe: Rot, Grün, Blau, Orange

Color: Red, green, blue, orange


LED

Standard Version			
LSU1005030	2x10W	E27 - A60 / LED	3450 gr.
Standard Version			
LSU1005031	1x9W	LED modul	4000 gr.
LSU1005032	1x13W	LED modul	4000 gr.
DALI DIMM Version			
LSU1005041	1x9W	LED modul	4050 gr.
LSU1005042	1x13W	LED modul	4050 gr.



Treiber der Leuchte ist in der Decke zu platzieren.
Deckenausschnitt: Ø90mm.
Driver of the luminaire is placed within the false ceiling.
Hole diameter for "driver" is Ø:90 mm.

Lichtkurven: www.lamp83.de
Light curves: www.lamp83.de




LED

Standard Version			
LSU1005130	2x10W	E27 - A60 / LED	5350 gr.
Standard Version			
LSU1005131	1x13W	LED modul	6000 gr.
LSU1005132	1x20W	LED modul	6000 gr.
DALI DIMM Version			
LSU1005141	1x13W	LED modul	6050 gr.
LSU1005142	1x20W	LED modul	6050 gr.

Treiber der Leuchte ist in der Decke zu platzieren.
Deckenausschnitt: Ø90mm.
Driver of the luminaire is placed within the false ceiling.
Hole diameter for "driver" is Ø:90 mm.

Lichtkurven: www.lamp83.de
Light curves: www.lamp83.de



Farbtemperatur Color Temperature K	Energieverbrauch Consumed power W	Lumen-Wert Lumen output lm (tj: 85°C)	Min. Farbwiedergabe Min. color rendering ra
2700	10	800	80
3000	9	1400	80
4000	9	1400	80
3000	13	1950	80
4000	13	1950	80
3000	20	2650	80
4000	20	2650	80

