



- Elektrostatisch pulverbeschichtet
- Metall-Körper
- Reflektor aus 99,8% purem Aluminium (T5 Version)
- Plexiglas
- Electrostatic powder coated
- Metal body
- 99,8% pured polished aluminium reflector (T5 version)
- Plexiglass

Farbe: sw (04), weiß (03), RAL9006 (00) Color: Black, white, metallic grey



Standard Version				
LSU1502003	1x40W	T5 FC	2Gx13	3000 gr.
LSU1502004	1x55W	T5 FC	2Gx13	3000 gr.

Bewegungssensor+Dimm / With motion detector+Dimm				
LSU1505007	1x40W	T5 FC	2Gx13	3050 gr.
LSU1505008	1x55W	T5 FC	2Gx13	3050 gr.



Externer Bewegungssensor+Dimm / External motion detector+Dimm				
LSU1505003	1x40W	T5 FC	2Gx13	3000 gr.
LSU1505004	1x55W	T5 FC	2Gx13	3000 gr.
L KT2401001	Externer Bewegungssensor / External motion sensor			352 gr.

LED

Standard Version			
LSU1502030	1x20W	LED modul	3050 gr.
LSU1502031	1x30W	LED modul	3050 gr.

DALI DIMM Version			
LSU1502040	1x20W	LED modul	3100 gr.
LSU1502041	1x30W	LED modul	3100 gr.

Lichtkurven: www.lamp83.de
Light curves: www.lamp83.de



Farbtemperatur Color Temperature K	Energieverbrauch Consumed power W	Lumen-Wert Lumen output lm (tj: 85°C)	Min. Farbwiedergabe Min. color rendering ra
3000	20	3200	80
4000	20	3200	80
3000	30	4500	80
4000	30	4500	80