



- Elektrostatisch pulverbeschichtet
- Metall-Körper
- Plexiglas
- Electrostatic powder coated
- Metal body
- Plexiglass

Farbe: sw (04), weiß (03), RAL9006 (00) **Color:** Black, white, metallic grey



Standard Version					
LSU1506001	1x40W	T5 FC	2Gx13	a:450 mm.	3250 gr.
LSU1506002	1x55W	T5 FC	2Gx13	a:450 mm.	3250 gr.



Standard Version					
LSU1506030	1x25W	LED modul		a:480 mm.	7500 gr.
LSU1506031	1x35W	LED modul		a:480 mm.	7500 gr.

DALI DIMM Version					
LSU1506040	1x25W	LED modul		a:480 mm.	7500 gr.
LSU1506041	1x35W	LED modul		a:480 mm.	7500 gr.



Standard Version					
LSU1508030	1x25W	LED modul		a:600 mm.	9000 gr.
LSU1508031	1x35W	LED modul		a:600 mm.	9000 gr.

DALI DIMM Version					
LSU1508040	1x25W	LED modul		a:600 mm.	9000 gr.
LSU1508041	1x35W	LED modul		a:600 mm.	9000 gr.

Standard Version					
LSU1509030	1x54W	LED modul		a:900 mm.	17000 gr.
LSU1509031	1x80W	LED modul		a:900 mm.	17000 gr.

DALI DIMM Version					
LSU1509040	1x54W	LED modul		a:900 mm.	17000 gr.
LSU1509041	1x80W	LED modul		a:900 mm.	17000 gr.

Lichtkurven: www.lamp83.de
Light curves: www.lamp83.de



Farbtemperatur Color Temperature K	Energieverbrauch Consumed power W	Lumen-Wert Lumen output lm (tc: 45°C)	Min. Farbwiedergabe Min. color rendering ra
3000	25	3350	80
4000	25	3550	80
3000	35	4250	80
4000	35	4550	80
3000	54	7850	80
4000	54	8350	80
3000	80	9900	80
4000	80	10550	80