


STRAIGHT | BAND LINEAR



W • lm	V	24 LED / m.	L
2,5 W • 135 lm	12 V	LSU1613001	260 mm.
5,0 W • 275 lm	12 V	LSU1613002	510 mm.
7,5 W • 415 lm	12 V	LSU1613003	760 mm.
10 W • 550 lm	12 V	LSU1613004	1010 mm.
36 LED / m.			
3,75 W • 200 lm	12 V	LSU1617001	260 mm.
7,50 W • 400 lm	12 V	LSU1617002	510 mm.
11,25 W • 600 lm	12 V	LSU1617003	760 mm.
15,00 W • 800 lm	12 V	LSU1617004	1010 mm.
72 LED / m.			
3,75 W • 275 lm	24 V	LSU1617005	260 mm.
7,50 W • 550 lm	24 V	LSU1617006	510 mm.
11,25 W • 825 lm	24 V	LSU1617007	760 mm.
15,00 W • 1100 lm	24 V	LSU1617008	1010 mm.
RGB LED			
2,5 W	24 V	LSU1609001	265 mm.
5,0 W	24 V	LSU1609002	515 mm.
7,5 W	24 V	LSU1609003	765 mm.
10 W	24 V	LSU1609004	1015 mm.



- Sehr dünne Aluminiumprofile in variierbaren Längen
- 50.000 Std. LED Lebensdauer
- Je nach Produkttyp 2.5W – 15W Leistung
- 135 – 1.100 Lumen (LED) je nach Länge
- Farbtemperatur 3000K – 4000K – RGB (CCT)

- Very thin aluminium profiles in varying lengths
- 50.000 hours life time LED power between 2.5W to 15W depending on the profile
- Based on length LED lumen output between 135 – 1.100 lm
- 3000K – 4000K – RGB (CCT) light color temperature