


STRAIGHT | WAY LINEAR



W • lm	V	Standard	L
4,2 W • 320 lm	12 V	LSU1621001	204 mm.
8,4 W • 640 lm	12 V	LSU1621002	364 mm.
12,6 W • 960 lm	12 V	LSU1621003	524 mm.
16,8 W • 1280 lm	12 V	LSU1621004	684 mm.
21,0 W • 1600 lm	12 V	LSU1621005	844 mm.
25,2 W • 1920 lm	12 V	LSU1621006	1004 mm.
29,4 W • 2240 lm	12 V	LSU1621007	1164 mm.
33,6 W • 2560 lm	12 V	LSU1621008	1324 mm.
37,8 W • 2880 lm	12 V	LSU1621009	1484 mm.



W • lm	V	Standard	L
4,2 W • 320 lm	12 V	LSU1622001	204 mm.
8,4 W • 640 lm	12 V	LSU1622002	364 mm.
12,6 W • 960 lm	12 V	LSU1622003	524 mm.
16,8 W • 1280 lm	12 V	LSU1622004	684 mm.
21,0 W • 1600 lm	12 V	LSU1622005	844 mm.
25,2 W • 1920 lm	12 V	LSU1622006	1004 mm.
29,4 W • 2240 lm	12 V	LSU1622007	1164 mm.
33,6 W • 2560 lm	12 V	LSU1622008	1324 mm.
37,8 W • 2880 lm	12 V	LSU1622009	1484 mm.



- Sehr dünne Aluminiumprofile in variierbaren Längen
- 50.000 Std. LED Lebensdauer
- 180° schwenkbare Varianten
- Abstrahlwinkel 90°
- Je nach Produkttyp 4,2W – 37,8W Leistung
- 320 – 2.880 Lumen (LED) je nach Länge
- Farbtemperatur 3000K – 4000K (CCT)

- Very thin aluminium profiles in varying lengths
- 50.000 hours life time LED power between 4,2W to 37,8W depending on the profile
- Versions with up to 180° adjustability
- 90° beam angle
- Based on length LED lumen output between 320 – 2.880 lm
- 3000K – 4000K (CCT) light color temperature