

## BRIGTH ANBAU / SURFACE MOUNTED



| W     | LED lm    | Standard   | DALI Dimm  |
|-------|-----------|------------|------------|
| 2x6 W | 2x755 lm  | LSU1811230 | LSU1811240 |
| 2x9 W | 2x1065 lm | LSU1811231 | LSU1811241 |


Da der Treiber nicht im Leuchtenkörper integriert ist, kann dieser nicht an der Betondecke montiert werden.

*Since its driver is not included inside the product body, it can not be mounted on concrete ceiling.*

Die innovative, elegante und effiziente BRIGTH Serie umfasst Versionen mit Einbau und Anbaumontage. Durch die schmale quadratische Bauform der Leuchten stellt sie Lichtperformance auf höchstem Niveau dar.

*An innovative, chic, efficient and minimalist product family to address the lighting needs of recessed and surface mounted forms: BRIGTH. A luminaire series which performs at highest level of illumination out of its very small square shaped bodies.*

Technische Zeichnung /  
Technical drawing (mm):



Deckenausschnitt /  
Ceiling cut (mm):



## TECHNISCHE EIGENSCHAFTEN / TECHNICAL SPECIFICATIONS:

|   |  |
|---|--|
| Gehäuse / Housing:  | Aluminium  |
| Oberflächenschutz / Surface protection:                       | Elektrostatisch pulverbeschichtet / Electrostatic powder coated  |
| Gehäusefarbe / Color housing:                                 | RAL9005, RAL9016, RAL9006  |
| Verstellbarkeit / Adjustability:                              | 350° horizontal drehbar, 20° vertikal schwenkbar /Adjustability 350° in horizontal axis and 20° in vertical axis |
| Abdeckung / Cover:  | Glas extra weiss / Glass extra white   |
| Lichtverteilung / Lighting distribution:                      | Reflektor / Reflector  |
| Abstrahlwinkel / Beam angle:                                  | 35° - 60°  |
| Blendlevel / Glare effect:                                    | N/A  |
| LED Lebensdauer / LED life time:                              | L80 50.000h  |
| Farbtemperatur / Color temperature (Kelvin):                  | 3000K / 4000K  |
| Farbwiedergabe / Color rendering index CRI (Ra):              | ≥90  |
| Mac Adam:   | Step 2-3   |
| Energieeffizienzklasse / Energy efficiency class:             | A+   |
| Photobiologische Sicherheit / Photobiological safety EN 62471 | RG 0-1   |
| Betriebsgerät / Control gear:                                 | Inkl. Kit  |
| Betriebsspannung / Operating voltage:                         | 220V AC ~ 240V AC  |
| Betriebsfrequenz / Operating frequency:                       | 50 ~ 60 Hz   |
| Optionen / Options:   | DALI Dimm, Casambi, Notlicht / Emergency, Automation   |

Farboptionen / Color options: ● ○ ●

3000K - 4000K • 1900 - 2350 gr

