



- Elektrostatisch pulverbeschichtet
- Aluminium-Körper stranggepresst
- 24° - 40° Optik Linsen

- Electrostatic powder coated
- Extruded aluminium body
- 24° - 40° optical lens options


Farbe: sw (04), weiß (03), RAL9006 (00)

Color: Black, white, metallic grey

LED

Standard Version				
LSU3005030	1x2W	LED	L: 51 mm	900 gr.
LSU3005031	2x2W	LED	L: 91 mm	1250 gr.
LSU3005032	4x2W	LED	L: 171 mm	1600 gr.
LSU3005034	10x2W	LED	L: 603 mm	2700 gr.
LSU3005035	16x2W	LED	L: 1500 mm	3800 gr.

DALI DIMM Version				
LSU3005040	1x2W	LED	L: 51 mm	950 gr.
LSU3005041	2x2W	LED	L: 91 mm	1300 gr.
LSU3005042	4x2W	LED	L: 171 mm	1650 gr.
LSU3005044	10x2W	LED	L: 603 mm	2750 gr.
LSU3005045	16x2W	LED	L: 1500 mm	3850 gr.



Lichtkurven: www.lamp83.de
Light curves: www.lamp83.de



IP 20

850°



Farbtemperatur <i>Color Temperature</i> K	Energieverbrauch <i>Consumed power</i> W	Lumen-Wert <i>Lumen output</i> lm (tj: 85°C)	Min. Farbwiedergabe <i>Min. color rendering</i> ra
3000	2	200	80
4000	2	200	80
3000	4	400	80
4000	4	400	80
3000	8	850	80
4000	8	850	80
3000	20	2100	80
4000	20	2100	80
3000	24	2500	80
4000	24	2500	80
3000	32	3350	80
4000	32	3350	80
3000	40	4150	80
4000	40	4150	80