

OPTIO ANBAU / SURFACE MOUNTED



W • lm	Standard	DALI Dimm	L (mm)
8 W • 850 lm	LSU3015032	LSU3015042	170
20 W • 2100 lm	LSU3015034	LSU3015044	608

LAMELLENMONTAGE / MOUNTED BETWEEN LAMELLAS

8 W • 850 lm	LSU3014032	LSU3014042	170
20 W • 2100 lm	LSU3014034	LSU3014044	608

W • lm	Holz/Wood	DALI Dimm	L (mm)
8 W • 850 lm	LSU3017032	LSU3017042	170
20 W • 2100 lm	LSU3017034	LSU3017044	608

LAMELLENMONTAGE / MOUNTED BETWEEN LAMELLAS

8 W • 850 lm	LSU3016032	LSU3016042	170
20 W • 2100 lm	LSU3016034	LSU3016044	608

**KOMBINATIONEN HOLZOPTIK / WOOD COLOR COMBINATIONS:**

Helle Kiefer / Light pine
BY101401



Dunkle Kiefer / Dark Pine
BY101402



Ahorn / Maple
BY101403



Walnuss / Walnut
BY101404

- Einbau-, Anbau-, Pendel- und Lamellenversionen
- Funktionales, innovatives, effizientes und komfortables Design
- Blendfrei ($UGR \leq 19$) und perfekte Lichtlenkung aus Linsenoptik- und Reflektorkombination
- Je nach Leuchte können 1-20 einzelne LEDs in Reihe mit je 2W verwendet werden
- Energieeffizienzklasse A + L80 50.000 Std. Lebensdauer
- 24 ° - 40 ° Abstrahlwinkel
- 3000K - 4000K (CCT) Farbtemperatur SDCM 3
- DALI Dimm Option, geeignet für Automatisierung (optional)

- Recessed, surface mounted, pendant and lamella versions
- Functional, innovative, efficient and comfortable design
- Low glare effect ($UGR \leq 19$) and perfect light control with optical lens and anodized metal reflector combination
- Depending on the luminaire, possibility to use between 1-20 single LEDs, each 2W
- Class A+ energy efficient & 50.000 hours life time LED
- 24° – 40° beam angle
- 3000K – 4000K (CCT) light color temperature SDCM 3
- DALI dim option, suitable for automation (optional)

Farboptionen / color options:

3000K - 4000K • 450 - 3850 gr



IP 20

850°

