



- Elektrostatisch pulverbeschichteter Metallreflektor
- Polycarbonat-Körper
- Befestigungsclips aus Polycarbonat oder Edelstahl
- gestärkter Polycarbonat-Diffusor opal


Farbe: grau

- Electrostatic powder coated metal reflector
- Polycarbonate body
- Polycarbonate or stainless steel mounting clips
- Strengthened opaque polycarbonate diffuser

Color: Grey

LED

Standard Version				
LSU3208030	17,6W	LED	3000K	2500gr.
LSU3208031	17,6W	LED	4000K	2500gr.
LSU3208032	17,6W	LED	6500K	2500gr.
LSU3208033	30,6W	LED	3000K	2500gr.
LSU3208034	30,6W	LED	4000K	2500gr.
LSU3208035	30,6W	LED	6500K	2500gr.
1 Std. Akku Batterie Pack / With 1 hour battery pack				
LSU3208050	17,6W	LED	3000K	3000gr.
LSU3208051	17,6W	LED	4000K	3000gr.
LSU3208052	17,6W	LED	6500K	3000gr.
LSU3208053	30,6W	LED	3000K	3000gr.
LSU3208054	30,6W	LED	4000K	3000gr.
LSU3208055	30,6W	LED	6500K	3000gr.
3 Std. Akku Batterie Pack / With 3 hours battery pack				
LSU3208060	17,6W	LED	3000K	3100gr.
LSU3208061	17,6W	LED	4000K	3100gr.
LSU3208062	17,6W	LED	6500K	3100gr.
LSU3208063	30,6W	LED	3000K	3100gr.
LSU3208064	30,6W	LED	4000K	3100gr.
LSU3208065	30,6W	LED	6500K	3100gr.



IP 65



LED

Farbtemperatur Color Temperature K	Energieverbrauch Consumed power W	Lumen-Wert Lumen output lm
3000	17,6	1900
3000	30,6	3060
4000	17,6	2000
4000	30,6	3220
6500	17,6	2000
6500	30,6	3220