



BAR AUßENBEREICH / OUTDOOR



W • lm	Standard	A
20 W • 2950 lm	LDA3002032	322 mm
40 W • 5850 lm	LDA3002035	622 mm



Montagehalterung / mounting bracket



- Besonderer Wallwasher-Effekt dank des Montagearms, der in verschiedenen Einstellungen einen präzisen Absenkbstand zwischen Leuchte und Oberfläche ermöglicht
- Außenleuchte mit IP65
- Energieeffizienzklasse A+, L80 50.000 Std. LED Lebensdauer
- Linsen Optik mit 12° - 18° - 30° - 40° Abstrahlwinkel
- 2.950 – 5.850 Lumen bei 20W - 40W Leistung
- Farbtemperatur 3000K – 4000K (CCT), SDCM 3
- Bis zu 180° vertikal schwenkbar
- Geeignet für Automatisierung (optional)

- Thanks to special mounting arm enabling precise setback distance between fixture and the wall surface in different levels, you can create a special wallwash effect
- An outdoor version of IP65
- Class A+ energy efficient & L80 50.000h life time LED
- Optical lenses with 12° - 18° - 30° - 40° beam angle options
- LED lumen output between 2.950 – 5.850 lm, 20 - 40W
- CCT light color temperature: 3000K - 4000K SDCM 3
- Adjustability up to 180° in vertical axis
- Suitable for automation (optional)

Farboptionen / color options:



3000K • 2500 - 3500 gr



IP 65

850°

