

LARINE PENDEL / PENDANT



STROMSCHIENENADAPTER / TRACK ADAPTOR

W	LED lm	Standard
4 W	600 lm	LSK1220030
6 W	830 lm	LSK1220031

EINBAU BASE / WITH RECESSED BASE A $\varnothing 75$


W	LED lm	Standard	DALI Dimm
4 W	600 lm	LSK1222030	LSK1222040
6 W	830 lm	LSK1222031	LSK1222041



ANBAU / SURFACE MOUNTED

W	LED lm	Standard	DALI Dimm
4 W	600 lm	LSK1221030	LSK1221040
6 W	830 lm	LSK1221031	LSK1221041

Technische Zeichnung /
Technical drawing (mm):



EINE FRISCHE BRISE VOM MEER

LARINE wurde so konzipiert, dass es die Erscheinung einer beleuchteten, gleitenden Möwe widerspiegelt. Die Hauptidee hinter LARINE war es eine hervorragend aussehende Designleuchte zu schaffen, die technisch korrektes Licht ausstrahlt

A FRESH BREEZE FROM THE SEA

ARINE was designed to reflect the grace of a sliding seagull into the space that you're illuminating. The main idea behind LARINE, was to create an outstanding looking luminaire that is emitting technically correct light.

TECHNISCHE EIGENSCHAFTEN / TECHNICAL SPECIFICATIONS:

Gehäuse / Housing:	Aluminium , Plexiglas-Flügel und Rahmen / Plexiglass wings and frame
Oberflächenschutz / Surface protection:	Elektrostatisch pulverbeschichtet / Electrostatic powder coated
Gehäusefarbe / Color housing:	RAL9005, RAL9016, RAL9006 + Flügel-Farben / Wing colors
Verstellbarkeit / Adjustability:	Starr / Not adjustable
Abdeckung / Cover:	Front transparent, seitlich matt / Front is transparent and side are is frosted
Lichtverteilung / Lighting distribution:	Reflektor / Reflector
Abstrahlwinkel / Beam angle:	35° - 60°
Blendlevel / Glare effect:	N/A
LED Lebensdauer / LED life time:	L80 50.000h
Farbtemperatur / Color temperature (Kelvin):	3000K / 4000K
Farbwiedergabe / Color rendering index CRI (Ra):	≥90
Mac Adam:	Step 2-3
Energieeffizienzklasse / Energy efficiency class:	A++
Photobiologische Sicherheit / Photobiological safety EN 62471	RG 0
Betriebsgerät / Control gear:	Inkl. Kit
Betriebsspannung / Operating voltage:	220V AC ~ 240V AC
Betriebsfrequenz / Operating frequency:	50 ~ 60 Hz
Optionen / Options:	DALI Dimm, Casambi, Automation

Flügel-Farben / Wing colors: ● ● ● Farboptionen / Color options: ● ○ ●

3000K - 4000K • 950 gr

